

Harlsan's latest development in blow down systems. Known for its robust performance, reliability and reduced maintenance costs, the Flotec Blow Down System boasts improved operational, safety and handling features to keep you drilling in the toughest situations.



At Harlsan we have a complete range of Blow Down parts and adaptor kits to suit most RC rigs. You can combine the Harlsan Blow Down, Wear Bend and Bearing Swivel for a complete above the head package.



KEY FEATURES AND BENEFITS

- Clearing ground water, rod string blockages and back flushing hole
- Improved sample purity
- Independent hydraulic actuator system
- Increased wear life and durability
- Lower cost of maintenance and extended service life cycle
- Threaded recesses for interated anchor point.
- Replaceable wear sleeves throughout
- Standard connections

TECHNICAL SPECIFICATIONS

**AUSTRALIAN MADE
TOUGHNESS**

Bore Size	50mm and 60mm
Dimensions	H270mm, L500mm, W160mm
Weight	65KG
Coupling Type	6" ACME to 4½" / Harlsan Flange to 4½" ACME
Hyd/Air Fitment [Up/Down]	HYD ¼" BSP, Air 1" BSP[up], 1¼" BSP [down]
Hyd/Air Fitment [Down]	HYD ¼" BSP, Air 2" BSP [down]



PERTH OFFICE

59 Edward St, Osborne Park Western Australia 6017
Telephone: +61 8 9201 9040



KALGOORLIE OFFICE

37 Kakarra Rd, Kalgoorlie Western Australia 6430
Telephone: +61 8 9021 1288