

TOXIC 6 GAS MONITOR

GX-6000 Six Gas with PID



- Smallest & lightest 6 gas monitor
- Smart sensor incl. PID, Infra Red & Toxics
- Wide operation temp. -20 to 50°C
- IP67
- Man down / panic alarm / LCD inversion / LED Flashlight
- IECEX Certified
- Calibration docking station
- 26 hour runtime

Infra Red

- CO2
- CH4
- Hydrocarbons

PID

- 10.6eV Lamp (ppb / ppm)
- 10.0eV Lamp
- 11.7eV Lamp
- PID Library of over 600 VOC's
- Benzene specific model available

Toxics


- Ammonia
- Chlorine
- Hydrogen Cyanide
- Nitrogen Dioxide
- Sulfur Dioxide
- Phosphine

AIR SAMPLING ACCESSORIES



Air Sampling Heads

Respirable Dust Sampling Heads



Cassettes

Filters

BOUNDARY MONITOR

GUARDIAN2: Multi-agent Monitoring Station



- Real-time particulate, noise, ground vibration(PPV)
- Optional VOC sensor
- Optional windspeed and direction sensor
- Web-hosted data with secure password
- Email and text alerts
- Wall or Pole mounted
- Powered by mains, solar or battery

PERTH



Unit 5 / 30 Enterprise Crescent, Malaga, WA 6090



0432 699 486 / 1800 174 536

BRISBANE



Unit 1 / 3 Deakin Street, Brendale, QLD 4500



07 3481 9000



sales@controlequipment.com.au



www.controlequipment.com.au

GAS DETECTION HYGIENE SOLUTION



Supplying and Servicing Gas Detection since 1977

NOISE

dBadge2



- Bluetooth connectivity
- Simple operation
- Rugged design
- Long battery life
- Colour display
- Motion sensing
- Pause function
- Measures all noise dose parameters simultaneously

AVAILABLE FOR HIRE

AIR SAMPLING PUMPS

APEX2: Personal Air Sampling Pump



- Flow range ml/min: 800-5000
- Low flow range ml/min: 5-500*
- Excellent battery life
- Weight 480 grams
- Charge time < 6 hours
- 2 Year Warranty
- IECEx and ANZEx certified

AVAILABLE FOR HIRE



DUST

DUST DETECTIVE



- Real-time graphical display of dust levels
- Simple icon driven user interface
- Extensive range: 0.001mg/m3 to 250g/m3
- Sampling for total dust, (respirable, PM2.5 or PM10 with optional adaptor)
- Long battery life
- Unique on site calibration insert
- Data logging with 500 run memory
- Downloads to Insight Software for analysis and reporting

SOUND

PUMP SERVICE

- 24hr turnaround time
- Most makes and models
- Fixed rate for repair
- Factory trained technician
- Casella authorised service agents

FIELD CALIBRATOR

Integrating Sound Level Meter (Class 2)



- Decibel (Db) Low Range (dB)20
- Decibel (Db) High Range (dB)140
- Resolution (dB)0.1
- Accuracy±1.0 dB
- ResponseFast, Slow, Impulse (simultaneously)
- WeightingA, C, Z (simultaneously)
- Meter ClassType 2
- OutputUSB
- DisplayFull Color Graphic
- Battery TypeAA Battery (3)
- Height (cm)23, Width (cm)7, Depth (cm)3
- DescriptionType 2 Sound Meter Kit

FLOW DETECTIVE: Personal Calibrator

LOW FLOW SAMPLING

VAPEX: Personal Low Flow Sampling Pump



- Flow range ml/min: 20 - 500
- Wireless Bluetooth Connectivity
- IECEx and ATEX certified
- Pocket size form factor
- Motions sensing technology
- Simple and smooth operation



- High accuracy calibration
- Pulsation detection
- Simple operation
- Rugged design
- Long battery life
- Wide flow measurement
- Bluetooth connectivity
- Closed loop, wireless calibration with Apex2 Pumps

CASELLA