

Wireless Dual Battery Powered Ambient Air Hazardous Gas Detector

LEADERS IN GAS DETECTION

OI-6900-O-2B Sensor Assembly

Since 1977

Reliable monitoring of hazardous gases in harsh conditions by use of the Otis wireless dual battery-powered detector.

The Otis Instruments Wireless OI-6900-O-2B Series Ambient Air Hazardous Gas Detector is a wireless, dual battery-powered instrument that uses an electrochemical or low-power infrared sensor element to detect a variety of toxic or combustible gases. The OI-6900 offers non- intrusive calibration while adjustments are made in the field. The OI-6900 continuously monitors the gas level of the surrounding environment and reports once a minute. The reporting rate will increase to once every five seconds when the detected gas is above the Background Gas Set-point. This set-point is adjustable to account for sites that may have a constant low level of gas always present. The display screen always shows the present gas concentration.





Туре	Range	T ₉₀	Warranty
CL2	0-10 ppm	_	12 months
СО	0-1000 ppm	< 210 sec.	24 months
H2S	0-100ppm	< 40 sec.	24 months
HCL	0-100 ppm	_	12 months
HCN	0-50 ppm	< 70 sec.	12 months
HF	0-10 ppm	_	12 months
LEL	0-100% LEL	< 50 sec.	24 months
NH3	0-100 ppm	_	12 months
NH3A	0-1000 ppm	_	12 months
NO2	0-20 ppm	_	12 months
02	0-25% vol.	_	24 months
PH3	0-5 ppm	< 55 sec.	12 months
SO2	0-20 ppm	< 95 sec.	24 months

Product Features

- Electrochemical or Low-Power Infrared Sensor
- Wireless Communication
- Dual Battery-Powered (Non-Rechargebale
- 1-Year Maximum Battery Life (Low-Power Infrared) or 2-Year Maximum Battery Life (Electrochemical)
- 102x64 Resolution Graphical LCD Screen;

 Transflective (Sunlight Readable) with LED Backlight
- 3 Magnetic Non-Intrusive Switches
- Non-Intrusive Calibration
- Adjustable Background Gas Setting
- Available with 900 MHz Radio
- Warranty on Hardware
- Sensor element warranty varies with gas type (See Gas List)
- Battery warranty is 90 days from product ship date
- IECEx Approval

Additional Features

■ Optional OI-501 Remote Sensor Kit with Enclosure

















FUMIGATION

Control Equipment Pty Ltd ABN 23 009 838 582

QLD:

Unit 1 / 3 Deakin St Brendale Qld 4500 Phone: (07) 3481 9000 sales@controlequipment.com.au

WA:

Unit 5 / 30 Enterprise Crescent Malaga WA 6090 Phone: 1800 174 536 www.controlequipment.com.au

Offices/Agents in:

Sydney Melbourne Adelaide Hobart Auckland Wellington



Product Specifications			
Sensor Type	Electrochemical or Low-Power Infrared Sensor		
Power Type	Dual Battery-Powered		
Operating Voltage	3.6 V (Non-Rechargeable)		
Battery Life	1-Year Max. Battery Life (Low-Power Infrared) or 2-Year Max. Battery Life (Electrochemical)		
RF Connection	External N-Female Radio Frequency (RF) Connector		
Display Screen	102x64 Resolution Graphical LCD Screen Transflective (Sunlight Readable) with LED Backlight		
Interface	3 Magnetic Non-Intrusive Switches for Calibration		
Customizable Settings	Adjustable Background Gas Setting (1% to 10% of Full Scale)		
T _{amb} Temperature Range	-40 to +54°C		
WireFree Radio Options	GEN II 900 MHz (200 mW)		
Product Dimensions	140mm. L x 155mm. W x 435mm. H		
Total Weight	2.7KG		
Remote Sensor Kit	OI-501 Remote Sensor Kit with Enclosure (7 pin)		
Additional feature	Available in lengths of up to 75m for Electrochemical and lengths of up to 12m for Low Power IR		
Hazardous Location Certifications and Approvals	Class I, Division 1, Group C and D, T6 Ex db IIB T6 Gb EX db mb ia [ia Ga] IIB T6 Gb Zone 1, AEx d IIB T6		
Hardware Warranty	12 Months		
Sensor Element Warranty	Varies with Sensor Element and Type (See List of Gases)		
Battery Warranty	90 Days from Ship Date		















DEFENCE





Control Equipment Pty Ltd ABN 23 009 838 582

QLD:

Unit 1 / 3 Deakin St Brendale Qld 4500 Phone: (07) 3481 9000 sales@controlequipment.com.au **۱۸/** ۸ ۰

Unit 5 / 30 Enterprise Crescent Malaga WA 6090 Phone: 1800 174 536

www.controlequipment.com.au

Offices/Agents in:

Sydney Melbourne Adelaide



